

RENTAL PRODUCT SPECIFICATION

Diesel Engine Generating Sets



Denyo DCA 400 SPKII



DCA 400 SPKII

ENGINE	
Make & Model	KOMATSU SA6D140
Type	Direct Injected, Turbocharged
Output Rating	50Hz PS/rpm : 485/1500 kW/min ⁻¹ : 517/565
No. of Cylinder-Bore x Stroke	6-140x165
Piston Displacement	15.24
Fuel	ASTM No.2 Diesel Fuel or Equivalent
Fuel Consumption	73 L/h(50Hz) - 87 L/h(60Hz)
Lube Oil Sump Capacity	74 l
Battery x Quantity	180G51 x 2
Fuel Tank Capacity	490Ltr

ALTERNATOR	
Frequency	50 Hz / 60 Hz
Continuous Output Rating	350Kva / 400Kva
Standby Output Rating	385/ 441
No.of Phases	3-phase, 4-wire
Rated Voltage*1	Dual Voltage
	0.8(Lagging)
	Within ± 0.5
Power Factor	Brushless, Rotating Exciter (with A.V.R)
Voltage Regulation	Class F
UNIT	
Dimensions (LxWxH)	4.2M x 1.4 M x 2.1 M
Dry Weight	5420kg
SOUND LEVEL	7m dB (A) 1500/1800 rpm (min-1)
	69(50Hz), 73(60Hz)



We Treasure Each & Every Customer

Who Supported Us

Throughout The Years

Our Company Is Committed

To Provide Excellent After Sales Service

To Our Valued Customers

